

Predator 2000-12 Cutterhead Dredge

Features:

Powerful, fuel efficient, offering the lowest overall operating costs

High Speed Low Torque Cutter Drive System

Fresh Water Cooling System

Three major Hull sections for easy transportability and assembly

Broad range of optional equipment to customize to your work

Dedicated diesel generator for AC power

Principal Dimensions:			Cutter			
			Hydraulic Motor/Gear Reduce	er cutter drive		
Ladder Length	42 Ft.	12.8 Mtr.	Power at cutter shaft	60 HP		
Overall Length, ladder up	77 Ft.	23.5 Mtr.	Cutter Shaft Diameter	3.75 In.	9.525	Cm.
Pontoon Length	60 Ft.	18.3 Mtr.	Cutter Speed	0-35 RPM		
Width, Outside	20 Ft.	6.1 Mtr.	Back Ring Diameter (I.D.)	31.5 In.	80.01	Cm.
Depth, Pontoons and Hull	5 Ft.	1.52 Mtr.				
Approx. Draft, with fuel	2.3 Ft.	0.7 Mtr.				
Working Depth (45 Deg)	30 Ft.	9.14 Mtr.	Winches			
Working Depth (60 Deg)	36 Ft.	11 Mtr.	Ladder: Line Pull	12,000 lbs.	5443.11	Kg.
Suction Pipe Diameter	14 In.	35.6 Cm.	Swing: Line Pull (x2)	12,000 lbs.	5443.11	Kg.
Discharge Pipe Diameter	12 In.	30.5 Cm.				
Dredge Pump			Spuds			
High Chrome 14x12- 36 " Impeller			Length	48 Ft.	14.63	Mtr.
4 Vane w/Cleanout Intake Tee			Diameter	16 In.	40.64	Cm.
			Weight	10,000 lbs. ea.	4535.92	Kg. each
Main Engine			Spud Cylinders			
Caterpillar Industrial Diesel Engine			Size	5 In. Dia.	12.7	Cm. Dia.
Heat Exchanger cooled			Length	30 In.	76.2	Cm.
750 BHP Continuous Power @1,800 RPM			Stroke	30 In.	76.2	Cm.
			Spud Travel	10 Ft.	3.05	Mtr.
Auxiliary Power			Deck Mounted Jib Crane			
Caterpillar Industrial Diesel Engine			Capacity	1 Ton		
Heat Exchanger Cooled			Reach	8 Ft.	2.44	Mtr.
250 BHP Intermittent Power			Operation	Manual		
Gear			Swing Width (40 degrees each side)			
Twin Disc Manual Clutch			@ 10 Degree Digging Angle	98 Ft.	29.87	Mtr.
Integral Clutch			@ 60 Degree Digging Angle	72 Ft.	21.95	Mtr.
Options			Theoretical Production Rate			
			Medium Sand, 15 % solids	262 yds ³ /Hr	239.57	
			Medium Sand, 25% solids	437 yds ³ /Hr	399.59	M ³ /Hr

Pioneer Dredge Inc. Jacksonville, FL - U.S.A. Tel: +1 904 503 9776 Email: sales@pioneerdredge.com