

## **Predator 2000-14** Cutterhead Dredge

## **Features:**

Powerful, fuel efficient, offering the lowest overall operating costs

High Speed Low Torque Cutter Drive System

Fresh Water Cooling System

Three major Hull sections for easy transportability and assembly

Broad range of optional equipment to customize to your work

Dedicated diesel generator for AC power

Principal Dimensions:			Cutter			
Time par Emiliana			Hydraulic Motor/Gear Reducer cutter drive			
Ladder Length	<b>42</b> Ft.	<b>12.8</b> Mtr.	Power at cutter shaft	<b>60</b> HP		
Overall Length, ladder up	<b>77</b> Ft.	<b>23.5</b> Mtr.	Cutter Shaft Diameter	<b>3.75</b> In.	9.525	Cm.
Pontoon Length	<b>60</b> Ft.	<b>18.3</b> Mtr.	Cutter Speed	<b>0-35</b> RPM		
Width, Outside	<b>20</b> Ft.	<b>6.1</b> Mtr.	Back Ring Diameter (I.D.)	<b>31.5</b> In.	80.01	Cm.
Depth, Pontoons and Hull	<b>5</b> Ft.	<b>1.52</b> Mtr.	, ,			
Approx. Draft, with fuel	<b>2.3</b> Ft.	<b>0.7</b> Mtr.				
Working Depth (45 Deg)	<b>30</b> Ft.	<b>9.14</b> Mtr.	Winches			
Working Depth (60 Deg)	<b>36</b> Ft.	<b>11</b> Mtr.	Ladder: Line Pull	<b>12,000</b> lbs.	5443.11	Kg.
Suction Pipe Diameter	<b>16</b> In.	<b>40.6</b> Cm.	Swing: Line Pull (x2)	<b>12,000</b> lbs.	5443.11	Kg.
Discharge Pipe Diameter	<b>14</b> In.	<b>35.6</b> Cm.	-			
Dredge Pump			Spuds			
High Chrome <b>16x14- 40</b> " Impeller			Length	<b>48</b> Ft.	14.63	Mtr.
4 Vane w/Cleanout Intake Tee			Diameter	<b>16</b> In.	40.64	Cm.
			Weight	<b>10,000</b> lbs. ea.	4535.92	Kg. each
Main Engine			Spud Cylinders			
Caterpillar Industrial Diesel Engine			Size	<b>5</b> In. Dia.	12.7	Cm. Dia.
Heat Exchanger cooled			Length	<b>30</b> In.	76.2	Cm.
<b>750</b> BHP Continuous Power @1,800 RPM			Stroke	<b>30</b> In.	76.2	Cm.
			Spud Travel	<b>10</b> Ft.	3.05	Mtr.
Auxiliary Power			Deck Mounted Jib Crane			
Caterpillar Industrial Diesel Engine			Capacity	1 Ton		
Heat Exchanger Cooled			Reach	<b>8</b> Ft.	2.44	Mtr.
<b>250</b> BHP Intermittent Power			Operation	Manual		
Gear			Swing Width (40 degrees each side)			
Twin Disc Manual Clutch			@ 10 Degree Digging Angle	<b>98</b> Ft.	29.87	Mtr.
Integral Clutch			@ 60 Degree Digging Angle	<b>72</b> Ft.	21.95	Mtr.
Options			Theoretical Production Rate			
			Medium Sand, 15 % solids	<b>318</b> yds <sup>3</sup> /Hr	290.78	M³/Hr
			Medium Sand, 25% solids	<b>530</b> yds <sup>3</sup> /Hr	484.63	M <sup>3</sup> /Hr

Pioneer Dredge Inc. Jacksonville, FL - U.S.A. Tel: +1 904 503 9776 Email: sales@pioneerdredge.com