

Predator 3000-16 Cutterhead Dredge

Features:

Powerful, fuel efficient, offering the lowest overall operating costs

High Speed Low Torque Cutter Drive System

Fresh Water Cooling System

Three major Hull sections for easy transportability and assembly

Broad range of optional equipment to customize to your work

Dedicated diesel generator for AC power

Principal Dimensions:			Cutter		
•			Hydraulic Motor/Gear Reduc	er cutter drive	
Ladder Length	52 Ft.	15.8 Mtr.	Power at cutter shaft	150 HP	
Overall Length, ladder up	92 Ft.	28 Mtr.	Cutter Shaft Diameter	5 In.	12.7 Cm.
Pontoon Length	70 Ft.	21.3 Mtr.	Cutter Speed	0-35 RPM	
Width, Outside	22 Ft.	6.71 Mtr.	Back Ring Diameter (I.D.)	43 In.	109.22 Cm.
Depth, Pontoons and Hull	5 Ft.	1.52 Mtr.			
Approx. Draft, with fuel	2.5 Ft.	0.76 Mtr.			
Working Depth (45 Deg)	37 Ft.	11.3 Mtr.	Winches		
Working Depth (60 Deg)	45 Ft.	13.7 Mtr.	Ladder: Line Pull	18,000 lbs.	8164.66 Kg.
Suction Pipe Diameter	20 In.	50.8 Cm.	Swing: Line Pull (x2)	18,000 lbs.	8164.66 Kg.
Discharge Pipe Diameter	18 In.	45.7 Cm.			
Dredge Pump			Spuds		
High Chrome 18x16- 40 " Impeller			Length	58 Ft.	17.68 Mtr.
4 Vane w/Cleanout Intake Tee			Diameter	24 In.	60.96 Cm.
			Weight	16,000 lbs. ea.	7257.48 Kg. each
Main Engine			Spud Cylinders		
Caterpillar Industrial Diesel Engine			Size	6 In. Dia.	15.24 Cm. Dia
Heat Exchanger cooled			Length	36 In.	91.44 Cm.
855 BHP Continuous Power @1,800 RPM			Stroke	30 In.	76.2 Cm.
			Spud Travel	12 Ft.	3.66 Mtr.
Auxiliary Power			Deck Mounted Jib Crane		
Caterpillar Industrial Diesel Engine			Capacity	2 Ton	
Heat Exchanger Cooled			Reach	10 Ft.	3.05 Mtr.
325 BHP Intermittent Power			Operation	Manual	
Gear			Swing Width (40 degrees each side)		
Twin Disc Manual Clutch			@ 10 Degree Digging Angle	117 Ft.	35.66 Mtr.
Integral Clutch			@ 60 Degree Digging Angle	85 Ft.	25.91 Mtr.
Heat Echanger Cooled					
Options			Theoretical Production Rate		
			Medium Sand, 15 % solids	419 yds ³ /Hr	383.13 M ³ /Hr
			Medium Sand, 25% solids	699 yds³/Hr	639.17 M ³ /Hr

Pioneer Dredge Inc. Jacksonville, FL - U.S.A. Tel: +1 904 503 9776 Email: sales@pioneerdredge.com